

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : G11B 7/00		A1	(11) International Publication Number: WO 91/20077
			(43) International Publication Date: 26 December 1991 (26.12.91)
(21) International Application Number: PCT/US91/04255		(74) Agent: KURTZ, Richard, E.; Woodcock Washburn Kurtz Mackiewicz & Norris, One Liberty Place, 46th Floor, Philadelphia, PA 19103 (US).	
(22) International Filing Date: 17 June 1991 (17.06.91)			
(30) Priority data: 539,625 18 June 1990 (18.06.90) US		(81) Designated States: AT (European patent), AU, BE (European patent), BR, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent), US.	
(60) Parent Application or Grant (63) Related by Continuation US 539,625 (CIP)		Published With international search report.	
(71) Applicant (for all designated States except US): BERNOULLI OPTICAL SYSTEMS, INC. [US/US]; 5700 Flatiron Parkway, Boulder, CO 80301 (US).			
(72) Inventors; and (75) Inventors/Applicants (for US only) : FARNSWORTH, Stephen, W. [US/US]; 801 Schofield Road, Berthoud, CO 80513 (US). WILSON, Scott, D. [US/US]; 1470 West 116th Avenue, Apartment #12, Westminster, CO 80234 (US).			

(54) Title: OPTICAL SERVO SYSTEM FOR MAGNETIC DISK



(57) Abstract

Coherent light (27) passing through slits (38, 40) produces an optical interference pattern (25) having a fringe spacing related to the spacing of the servo tracks on a magnetic disk (10). The convolution of the interference pattern with the servo tracks (12, 13) generates a servo error signal (19).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

OPTICAL SERVO SYSTEM FOR MAGNETIC DISK

This application is a continuation-in-part of U. S. Application Serial No. 539,625, filed June 18, 1990 (Attorney's Docket No. BOSC-8903).

5 **FIELD OF THE INVENTION**

The present invention relates to information storage systems and more particularly to an optical sensor and a system for tracking the position of a head with respect to data tracks concentrically, or spirally, spaced
10 about the rotational axis of a disk.

BACKGROUND OF THE INVENTION

The present emphasis in the development of information storage systems is the capability to store more and more information into a so-called "desk top" sized
15 computer memory system. Those "desk top" sized memory systems which incorporate magnetically recorded hard disk media, such as that used in Winchester disk drive type memory systems, currently have the capacity to store upwards of 20 megabytes of magnetically recorded
20 information. The problem with such memory systems is that by necessity the hard disk media is permanently mounted into the computer. Since the media is not easily removable, the use is limited to whatever portion of the hard disk is remaining for information storage at the time
25 of use. Accordingly, magnetically recorded hard disk media information storage systems are not viewed as a potential solution to increasing information storage capacity.

So-called "floppy" disk memory systems wherein flexible disks, each having a diameter of either 5.25

-2-

inches or 3.50 inches, are used as the storage media provides easily removable storage media. However, the problem with such storage systems is that the present storage capacity of information magnetically recorded on a single floppy disk used in such a system has not yet reached a level equal to that of the hard disk, i.e., a single floppy disk media can only store approximately 1 to 2 megabytes of magnetically recorded information.

Systems for storing information which can be accessed through optical devices have received significant attention due to their potential capacity to store substantially more data, i.e., on the order of 400 to 800 megabytes of information, than that available in either magnetically recorded hard disk or floppy disk storage systems.

The improved capacity of optical memory is obtained at a higher cost for the media, as well as for the drive when compared to magnetic memory devices. New advances in barium-ferrite (BaFe) magnetic media allows bit densities to exceed optical bit densities. However, track densities of removable magnetic media are many times less than their optical counterparts.

A disk drive which uses an optical track sensing technique to determine the radial position of a magnetic head on a disk has been used to allow higher track densities. One such system is described in AN INTRODUCTION TO THE INSITE 325 FLOPTICAL® DISK DRIVE, Godwin, in a paper presented at the SPIE Optical Data Storage Topical Meeting (1989). This disk drive uses disks containing prewritten optical tracks with a 20 micron pitch. A light emitting diode illuminates the disk. The image of the disk's surface is transferred to a four-element photodetector by a lens and mirror. Such a system has the following drawbacks.

Because the INSITE head uses an L.E.D. as a diffused illumination source, light intensity at the disk, and subsequently on the detector, is very low. This

-3-

creates a very low level tracking signal which must be greatly amplified electronically. Any system noise at this point also gets amplified and a signal with a high degree of undesired noise is obtained.

5 The INSITE head senses a very short segment of only two tracks. Since such a small area of the tracks is being detected, then flaws in the disk such as small debris, scratches, roughness of the edges of the optical tracks, or even reflectivity variations all contribute to noise.

10 The head of the INSITE optical system creates a magnified image (5.5X) of the surface of the disk with a very short depth of focus ($\pm 6 \mu\text{m}$). Because of this short depth of focus, the tracking signals degrade very quickly in the presence of shock, vibration, and thermal expansion
15 within the head. INSITE includes a bi-metallic mechanism to compensate for thermal expansion and index of refraction changes within the optical system.

SUMMARY OF THE INVENTION

20 It is an object of the invention to provide a sensor and an optical tracking system which obviates the foregoing disadvantages in prior disk storage systems.

 It is an object of the present invention to provide a magnetic disk storage system with a high track density made possible by using an optical track sensing
25 system which is relatively insensitive to noise, shock, vibration and thermal expansion.

 In accordance with the present invention, an optical interference pattern having a fringe spacing related to the spacing between the servo tracks is incident
30 on the disk. A servo error signal which is the convolution of the interference pattern and the servo tracks is generated. This servo error signal controls the positioning of the magnetic head with respect to the data tracks.

35 The invention has the following advantages over prior optical tracking systems.

-4-

A high intensity spot is incident on the disk surface and re-imaged at the detector. This yields a much higher level tracking signal requiring less amplification. The resulting tracking signal has less noise when compared
5 to the INSITE head, for example.

In the invention, the tracking signal is created by sensing a larger area of the disk. The pattern covers an area several tracks wide and several microns long. The reason for detecting a larger area of the disk is to reduce
10 the noise caused by small flaws in the disk or edge roughness in the pre-written servo tracks. This is achieved by effectively averaging the tracking signal over several tracks on the disk at once. An extremely long depth of focus (greater than 1 mm) makes the system
15 insensitive to disk axial runout, shock, vibration, thermal expansion and other thermal changes.

In accordance with another aspect of the invention, the high intensity spot interference pattern is incident upon a fixed grating instead of being incident
20 directly on the disk itself. This grating, or encoder, has a "flag" area which indicates the zero position of the magnetic head. When the optical servo system senses the flag area, an indication is produced that the head is at the zero, or reference, position. This is used to reset
25 the radial position counter of the disk drive.

Further in accordance with the present invention, the optical system of the present invention includes holographic optical elements. These holographic optical elements and a lens are molded on a block of transparent
30 plastic which provides temperature compensation for the optical elements.

In accordance with a further aspect of the invention, the optical servo system includes integrated optical elements which are attached to, and form a
35 monolithic structure with, the magnetic head which reads the data tracks.

-5-

The foregoing and other objects, features and advantages of the invention will be better understood from the following more detailed description of a particular embodiment.

5 DESCRIPTION OF THE DRAWINGS

Fig. 1 depicts a disk storage system and an optical tracking system in accordance with the present invention;

Fig. 2 shows a portion of a disk with the pattern
10 of the servo tracks and the interference pattern thereon;

Fig. 3 shows a layout of the tracking system of the present invention;

Fig. 3A shows the HOE implementation;

Fig. 4 shows the two slits producing an
15 interference pattern;

Fig. 4A depicts the width and spacing of the slits;

Fig. 4B shows the relationship between the interference pattern and the width and spacing of the
20 slits;

Fig. 5 is an exaggerated enlargement of the interference pattern;

Fig. 6 depicts the optical interference pattern in relation to the servo track;

Fig. 7A depicts the reflectivity of the servo
25 tracks as a function of disk radius;

Fig. 7B depicts the light intensity of the optical interference pattern as a function of disk radius;

Fig. 8 and 8A depict the prism breaking the
30 optical interference pattern into two optical patterns;

Fig. 9 and 9A show the HOE implementation in more detail;

Figs. 10A and 10B depict the two reflected optical patterns;

-6-

Figs. 11A and 11B depict the quadrature servo error signals generated by the binary cell photodetector; and

Fig. 12 shows an alternate embodiment with an optical encoder; and

Fig. 12A depicts the quad cell photodetector of Fig. 12.

Fig. 13 is similar to Fig. 12, but further shows the servo system used to reset the radial track counter;

Fig. 14 shows the flag area on the encoder grating;

Fig. 15A shows the servo error signal produced as the spot 53 traverses the portion 56 of the encoder;

Fig. 15B shows the other, non-flagged, servo error signal;

Fig. 16 shows an alternate embodiment of the flag area;

Fig. 17A shows the servo error signal as the spot traverses the flag area of the encoder of Fig. 16;

Fig. 17B shows the other, non-flagged, servo error signal;

Fig. 18 depicts an alternate embodiment in which a separate interference pattern, or spot, traverses the flag area on the encoder;

Fig. 18A shows the servo error signal as the spot 53 traverses the grating of Fig. 18;

Fig. 18B shows the servo error signal as the spot 54 traverses the grating;

Fig. 18C shows the signal produced as the spot 64 traverses the grating of Fig. 18;

Fig. 19A is an edge view of a plastic block on which holographic elements and lenses are molded;

Fig. 19B is a bottom plan view of the plastic block of Fig. 19A;

Fig. 20A is a cross-section view of an integrated optics head with attached magnetic head;

-7-

Fig. 20B is a partial rear view of the heads of Fig. 20A;

Fig. 20B is a bottom isometric of the monolithic structure of Fig. 20A.

5 DESCRIPTION OF THE PREFERRED EMBODIMENT

Fig. 1 shows a magnetic disk storage system for reading data from or writing data to a removable disk surface 10 having a rotational axis 11 and a plurality of data tracks. Servo tracks 12, 13 and others form an
10 optical pattern concentrically recorded with said data tracks. Alternatively, the servo tracks may be a spiral pattern.

The disk is rotated about its axis 11 by a drive which is not shown. A read/write head 15 is positioned
15 adjacent to the disk surface for reading or writing. An actuator 17 positions head 15 with respect to the disk surface. A servo system 19 controls actuator 17. The servo system is responsive to a servo error signal generated by the optical detector 21.

20 In accordance with the present invention, an optical interference pattern is generated by the optics 23 which is mounted rigidly with read/write head 15. The interference pattern is incident on the servo tracks of the disk immediately next to write head 15. The reflected
25 light is the convolution of the interference pattern and the pre-recorded servo tracks. This light is detected by the optical detector 21 to produce the servo error signal.

Fig. 2 depicts a portion of magnetic disk 10. The pre-recorded servo tracks are shown at 12 and 13. The
30 optical interference pattern 25 has fringes which have a spacing approximately equal to the spacing of the servo tracks.

Referring to Fig. 3, a low power 780 nm laser diode 27 emits coherent light which is gathered by the
35 collecting lens 29. An aperture plate 31 has two slits producing two crossed beams of coherent light. A prism 33 splits the laser beam in the direction orthogonal to the

-8-

two interfering beams. Prism 33 covers half of the light passing through each slit. Prism 33 rotates half of the beam slightly so that two interference patterns appear in the focal plane of the lens 35. The spots of coherent light are incident upon the disk 10. Incident light is convolved with the pre-recorded optical pattern of the servo tracks on the disk 10. The reflected light is imaged by imaging lens 37 on the binary cell photodetector 39. The two cells detect the two reflected light patterns to produce quadrature signals which are used as the servo error signal.

As shown in Fig. 4, light passing through spot forming lens 35 is split into two paths of light by the aperture plate 31. An interference pattern of several cycles is created at the focal plane of the lens system. The spatial frequency of the interference pattern is determined by the relative angle of the two crossed beams.

The optical components in the invention can include or be mostly replaced by a multi-zoned Holographic Optical Element ("HOE"), or a multi-zoned replicated optic. The first described embodiment includes a collimator lens, a pair of slits, a prism, and (for the return beam path) a collector lens. All four of these devices or some subset of them can be replaced by either a HOE or an all refractive multi-element array of similar format. Fabricators of such custom HOE's are able to computer-generate and E-beam etch surface relief patterns for replication, and utilize "blazing" as in diffraction gratings to increase light efficiency.

Fig. 3A shows an embodiment in which HOE 36 replaces the lenses, slits and prism of Fig. 3.

Note that a surface embossed hologram with "blaze" is really a cross-over technology device, wherein refraction and diffraction both are used to direct light paths. It combines the function of a Fresnel lens (all refractive) and non-blazed holograms which work strictly by diffraction. Embodiments including the discrete optical

-9-

devices or the multi-element combinations whether refractive, diffractive, or in combination (i.e., "blazed hologram") are all within the scope of the invention.

In the specific embodiment being described, the slit spacing and lens focal length are selected to provide a 2.2° beam angle using a wavelength of 780 nm. As an example, the pitch, i.e., the spacing between the data tracks and the spacing between the servo tracks is approximately 20 microns. In this example, an interference pattern having several cycles of fringes is produced with a spacing between the fringes which is equal to the pitch of the data and servo tracks. A multiple of the relationship between fringe spacing and pitch of the tracks can be used.

Fig. 4A depicts the slits 38 and 40 in the aperture plate 31. The slits have a width w and a spacing d .

Fig. 4B depicts the relationship between the fringes of the interference pattern and the width and spacing of the aperture plate. The length l of the interference pattern is inversely proportional to the width w of the slits and the spacing between the fringes is inversely proportional to the distance d between the slits.

Fig. 5 shows the interference region enlarged and exaggerated to show the advantage of the present invention. An interference pattern is produced throughout the region which has been denoted 41. Because the pattern exists throughout this region, there is no need to focus the light on the disk surface. Rather, as long as the disk surface is in the region 41, the proper interference pattern is incident upon the optical tracks. This long depth of focus, which is about 1mm in the embodiment being discussed, makes the system insensitive to disk axial runout, shock, vibration, thermal expansion and other thermal changes and relaxes manufacturing tolerances. The overlap of the two beams is where the interference pattern exists. The three ellipses point out the extent of

-10-

the overlap (and hence of the interference pattern) for 3 different focal positions.

Fig. 6 depicts the interference pattern 25 produced by the slits in relation to the pre-recorded optical pattern formed by the servo tracks.

Fig. 7A depicts the reflectivity R of the servo tracks as a function of the radius of the disk.

Fig. 7B shows the intensity I of the optical interference pattern as a function of disk radius r . When the light of the optical interference pattern is reflected from the disk surface, the reflected light is the convolution of incident light intensity and reflectivity of the servo tracks. This is specified by the well-known convolution integral:

$$\int_0^s \int_0^t I(s-x, t-y) \cdot R(x, y) dx dy$$

While the reflection of light has been shown in the specific embodiment, light could be transmitted through the disk. Similarly, the result will be the convolution of the intensity of incident light with the servo pattern. In this case, it is the transmissivity of the medium, rather than the reflectivity, which is convolved with the incident light.

Fig. 8 shows how the prism 33 splits the interference pattern into two spots. Prism 33 covers half of the light passing through each slit. Prism 33 is rotated slightly in the direction indicated by arrow 43 to move one of the spots in the cross track, or radial, direction in order to change its phase relative to the first spot. The prism is adjusted to achieve a 90° phase shift and locked in place. In the embodiment under consideration, less than approximately one degree of rotation is required to achieve a 90° phase shift.

Fig. 8A shows the wedge cross-section of prism 33 and the beam bending action. This shows how the prism alters the location of one spot.

-11-

Figs. 9 and 9A show the holographic implementation in more detail. The HOE 36 has an area 36A which replaces lens 29, slits 31, prism 33 and lens 35. The area 36B replaces the lens 37. Fig. 9 also shows the mirror 44 directing light onto the surface of media 10 and back to detector 39.

Figs. 10A and 10B depict the two interference patterns which are 90° out of phase with respect to a cycle of the servo tracks.

Fig. 11A depicts the sinusoidal signal produced by the photodetector as a function of distance in the radial direction. Fig. 11B depicts the other output of the photodetector which is a sinusoidal signal 90° out of phase with respect to the first signal. These two signals form a quadrature pair which are used in a servo system in a manner known in the art.

The optical head device of the invention can be used with a grating or ruling of the type used in linear position encoders. This is accomplished by making the optical channel "dual channel," projecting pairs of spots both onto the media disk and also onto a ruling pattern fixed inside the mechanism acting as a stationary reference scale. The same optical head collects the return light beams from both channels and produces two sets of position signals, for: a) position relative to the media disk data tracks, and b) for position relative to the drive's main framework, i.e., in terms of absolute radius from the spindle center. In this way, the same system provides both the capability of tracking the laser marked media or behaving as a conventional floppy disk drive in positioning by absolute radius from the spindle. The benefit is that with this dual channel detection system plus a dual transducer magnetic head (wide and narrow track) the drive can be made "downward compatible", that is, can be made to read and write both the new (e.g., 20 MByte) and the old (e.g., 1.4 MByte) media.

-12-

Fig. 12 shows such a two channel system. HOE 46 projects four spots which are reflected from mirror 47 onto the disk surface 10 and onto the fixed-scale surface 48 which is like a linear encoder. The reflected light, two spots from disk 10 and two spots from fixed scale surface 48, are re-imaged on the four elements of a quadrant photodetector 50, often referred to as a "quad cell photodetector."

Fig. 12A depicts the four spots incident on the quad cell photodetector 50. The top two spots are reflected from the disk with one of the spots being 90° out of phase with the other. The bottom two spots are reflected from the fixed scale surface 48 with one spot being 90° out of phase with the other.

The second set of slits to make the second set of spots for the fixed scale surface 48 is positioned at closer spacing than the first, in what was in the single channel embodiment the opaque dead zone between slits, and utilizing light which was wasted before. Note that fringe spacing is inversely proportional to the slit spacing, so the second channel spots have a larger fringe spacing. The spacing is picked to be related to the standard track pitch of the old floppy format so the second channel can be used for locating to that format. A ruled grating of pitch matching the fringe spacing is generated and mounted parallel to the media, aligned parallel to the carriage travel. The optical head directs the two pairs of beams at slightly different angles to get slight vertical separation at the surface of the turn mirror 47. The turn mirror for this version is "delta shaped", having two facets to turn one pair of beams up and the other down -- one to the disk, the other to the fixed scale.

"Differential Read" or "Common Mode Rejection" can be achieved in accordance with the invention. For each pair of spots giving quadrature signals in the embodiments described to this point, we can generate instead 4 spots, each 90° of phase apart; now the signals are paired and

-13-

differenced, to give two quadrature signals with the "dc" component subtracted out. The reflectivity variations and light level variations are much less of a signal processing problem. A much simpler AGC, if any, is required.

5 Fig. 13 shows how the servo signal generated by the fixed scale surface 48 is used to reset the radial track counter 41. (In Fig. 13, the quadcell photodetector 50 has been shown facing the viewer, instead of the correct edgewise view of Fig. 12.) In Fig. 13, all elements in the
10 optical head housing 55 are enclosed in a dashed line box labeled 55.

 Normally, in a disk drive such as the standard 3.5 inch 1.44 MByte floppy, a track zero sensor is required. This device indicates precisely when the
15 carriage is at a reference radius so a radial position counter 51 can be zeroed. This enables a drive to precisely calibrate radial position each time it powers out. Eliminating the conventional electro-mechanical track zero sensor makes a significant savings in cost and space.

20 In the simplest embodiment, only the encoder scale grating 48 needs to be modified. The remainder of the optical sensor remains as previously described.

 Fig. 14 shows the two optical interference patterns, or spots, 53 and 54 which are incident upon the
25 encoder fixed scale grating 48 which includes successive light and dark bars. The grating 48 includes a first portion 56 which includes a "flag area" 58 in the path of spot 53. An isolated edge identifies the reference (or zero) radius 59 of the head on the disk. The portion 57 of
30 the encoder grating does not have the flag area. It is traversed by the spot 54.

 Fig. 15A shows the servo error signal produced as the spot 53 traverses the portion 56 of the encoder grating.

35 Fig. 15B shows the servo error signal produced when the spot 54 traverses the area 57 of the encoder grating 55.

-14-

The waveform of Fig. 15A is produced as the encoder spot 53 runs off the regular grating through the flag area. First an interval occurs where the sinusoidal modulation is still evident, but is dropping in amplitude to zero. Then, when the light spot 53 crosses the isolated edge in the center of the flag 58, the signal is a ramp with steps. The isolated edge is at the reference radius 59. The servo system 19 discriminates the point at which the spot 53 is crossing the reference radius. The trigger 52 resets the radial track counter 51 repeatably from this waveform. Then radial position is counted from there using only the sine wave signal (Fig. 15B) from spot 54 until the flag spot 53 acquires a normal sine wave signal when it runs off the flag. This means that a quadrature pair of signals is not available for the distance (about ten tracks worth) between the isolated flag edge 59 and the normal encoder scale area, so correct distance measurement through that interval depends on knowledge of the direction of travel, and hence is only reliable while the carriage is flying toward the inner diameter counting the cycles of the single sine wave signal it is getting.

Another embodiment of the flag is shown in Fig. 16 wherein the grating 48 has a flag area 60 at the end of the encoder consisting only of a void. As in the case of Fig. 14, the flag area is approximately half the width of the encoder grating and is disposed such that only one of the spots, the flag spot 53, moves across it, and so that the edge of the flag is located essentially at the position where the light spots fall when the carriage is at the reference radius. Therefore, when the spot 53 is moving across the edge into the void, the sinusoidal servo error signal falls to about half amplitude just at the time when the carriage is at the reference radius. This is indicated at 61 in the sinusoidal servo error signal shown in Fig. 17A. Fig. 17B shows the normal undisturbed servo error signal produced by the spot 54, in quadrature with the spot 53. The servo system 19 triggers from these two waveforms,

-15-

but both signals are present and usable with their quadrature relationship, so the servo system 19 has full information regardless of the disk runout or carriage direction.

5 Fig. 18 shows another embodiment using a separate spot 64 which passes through a separate flag area 65 on the encoder grating. An additional photodetector is required for this embodiment. In the holographic optical element embodiment of the invention, the HOE has a zone which
10 creates the additional spot 64 narrowly focused in the radial direction beside or between the other two encoder spots 53 and 54. The encoder has a flag 65 that intercepts only the spot 64. The flag can be the void type shown in Fig. 16, or it can be of the type shown in Fig. 14. The
15 servo signal in this embodiment has a steep, easy to trigger edge occurring at the reference radial position 59 while the other two encoder signals are at full and unchanging amplitude in their quadrature relationship.

 Fig. 18A shows the servo error signal produced as
20 the spot 53 traverses the grating and Fig. 18B shows the servo error signal produced as the spot 54 traverses the grating. Fig. 18C shows the signal produced when the spot 64 traverses the void 65 and particularly shows the sharp edge produced as the spot passes the reference location 59.

25 Figs. 19A and 19B show the holographic optical elements 71, the collimator lens 72 and the condenser lens 73 molded on a clear plastic blank. This embodiment of the invention provides for thermal compensation.

 Laser diodes characteristically change wavelength
30 with temperature, which gives the problem that the focal plane of a hologram shifts from the wavelength change as temperature of the laser changes. The range of temperature in which the optical tracking sensor of the invention works is several tens of degrees centigrade, enough to cause
35 about 10 nanometers wavelength shift and enough focus shift to degrade the signal amplitude significantly. Similarly, a thermal shift problem is inherent with the embodiment

-16-

using molded plastic lenses instead of a HOE. In this case, the primary contributor is the rate of change of diffractive index with temperature rather than the change of index with laser wavelength. The two phenomena have
5 opposite sign. It is therefore possible to fashion a temperature compensated optical device analogous to the HOE which has ray bending power both in a holographic element and a molded plastic refractive element which has essentially zero focal plane shift with change of
10 temperature of the head.

This combination device is molded into the rectangular block of transparent plastic with the HOE features 71 molded into one flat surface, but with the addition of lenslet bulges 72 and 73 molded into the
15 opposite surface.

The temperature problem and the features of the invention that compensates for it are described below. With just a holographic element and a laser diode in an aluminum housing the contributions to the change of image
20 focal distance with a RISE in temperature are:

1. Wavelength of laser INCREASES, decreasing focal length of hologram, making distance to image DECREASE.
- 25 2. Material between the laser and hologram expands, INCREASING distance of source from hologram, DECREASING distance to image focus.
- 30 3. Physical size of the hologram expands, INCREASING (slightly) its focal length, INCREASING distance to image focus.
- 35 4. Physical length of the housing between the hologram and the media surface, the desired image focal plane, expands (a small amount), so it is a "moving target." If the head is properly temperature compensated, the change of image location from 1 through 3 above will be an INCREASE equal to this.

-17-

Th similar list for a plastic lens version of the optical head has almost the same list, except for one difference: Item 1 changes, with two parts:

- 5 a. Index of refraction of the lens DECREASES, causing the focal length of the lens to INCREASE and distance to image focus to INCREASE .
- 10 b. Index of refraction of the lens depends on wave length slightly, such that with the INCREASE of wavelength with temperature the index DECREASES, lengthening the focal length and causing the distance to image to INCREASE.

15 Part 1 is dominant in the HOE case and Part 1a in the plastic lens case, so the defocus goes from a large decrease to a large increase.

Actual calculations for one working embodiment of the invention show that for the HOE-only system a 40 degree centigrade rise in temperature causes the image focal plane
20 to change about -2.6 mm relative to the media plane (minus indicates decrease), an unacceptably large amount. The plastic lens version gets about +2.2 mm change, almost as large but in the opposite direction. This circumstance lends itself to the compensation method of making a
25 combination where about half the lens power is in a plastic lens and the rest in the holographic element, prorated so their changes with temperature cancel. The following example illustrates the invention.

Fig. 21 shows a ray path through a curved
30 surface, the plastic lens surface, then bending at the second flat surface at a point labeled "R". This is the bend by diffraction of the lines of the HOE, and "R" stands for the center-to-center spacing of the lines, given in units microns, abbreviated μm .

35 Assume the following param ters, all at room temperatures:

$$R = 8.148 \text{ mm}$$

-18-

	THK	=	1.500 mm
	N	=	1.572791
	$\frac{dN}{dT}$	=	$-14 \cdot 10^5 / ^\circ\text{C}$
5	$\alpha(\text{Plastic})$	=	$10 \cdot 10^{-6} / ^\circ\text{C}$
	$\alpha(\text{AL.})$	=	$23.4 \cdot 10^{-6} / ^\circ\text{C}$
	$\frac{d\lambda}{dT}$	=	$.25 \text{ nm} / ^\circ\text{C}$
	λ	=	$.79 \text{ }\mu\text{m}$
10	θ_5	=	1.109°
	Z_2	=	37.805 mm
	θ_0	=	$6/253^\circ$
	Γ	=	$13.6 \text{ }\mu\text{m}$

The following parameters can be computed:

15 $Y_1, \Gamma, \theta_1, \theta_2, \theta_3, \theta_4.$

These parameters are computed from the eight formulas describing:

1. Input Geometry;
2. Sag of Curve;
- 20 3. Refraction;
4. Inside Geometry;
5. Thickness;
6. Diffraction;
7. Internal Angles; and
- 25 8. Output Geometry

Since $R, \text{THK}, \lambda, N, \theta_0, \theta_5,$ and Z_2 were chosen, one way to solve the problem is to find Y_1 numerically on a computer.

The resulting embodiment is:

30	R	=	8.148mm
	THK	=	1.500mm
	N	=	1.572791

-19-

	λ	=	.79 μm
	θ_1	=	6.253°
	θ_5	=	1.109°
	Z_2	=	37.805mm
5	$(Y_2$	=	.7318mm)
	Y_1	=	.6748mm
	θ_2	=	.115 radians
	θ_3	=	.0829 radians
	θ_4	=	.03874 radians
10	S_1	=	.02799 mm
	Γ	=	13.6018 μm
	Z_1	=	6.1305 mm

- Starting with this embodiment at room temperature, the change in focus relative to the disk can
- 15 be calculated. Suppose $\Delta = +20^\circ\text{C}$. The following occur:
- Index of refraction, N , changes (decreases).
 - Radius of curvature, R , changes (increases).
 - Z_1 expands (increases)
 - THK expands (increases)
 - 20 - Y_2 expands (increases)
 - Γ expands (increases)
 - Laser wavelength increases (increases)
 - Z_2 expands (increases)

-20-

EXPANSION OF Z_2 :

$$\Delta Z_2 = Z_2 \cdot \alpha_N \cdot \Delta T$$

$$= (37.805) (23.4 \cdot 10^{-6}) (20^\circ) = .018 \text{ mm.}$$

Let Z_3 = Axial Position of Focussed Spot.

5 ΔZ_3 can be calculated for $\Delta T = +20^\circ \text{C}$.

Formula No. 8 now becomes:

$$\tan \theta_3 = \frac{Y_2}{Z_3}$$

10 With temperature change:

$$R = 8.148 \text{ increases to } 8.1594$$

$N = 1.57279$ changes to 1.56999 (more correctly the change in the index of refraction should be:

15 $\frac{dN}{dT} \Delta T + \frac{dN}{d\lambda} \cdot \frac{d\lambda}{dT} \Delta T$)

$$\text{THK} = 1.500 \text{ increases to } 1.5021$$

$$\lambda = .790 \text{ increases to } .795$$

$$Y_2 = .7318 \text{ increases to } .7329$$

$$r = 13.6018 \text{ increases to } 13.6208$$

20 $Z_1 = 6.1305 \text{ increases to } 6.1334$

By a similar method, described above, Y_1 , the angles, and Z_3 are obtained.

$$Y_1 = .67533$$

$$\theta_3 = 1.110^\circ$$

25 $Z_3 = 37.8228 \text{ mm}$. This is an increase of $\Delta Z_3 = +.018 \text{ mm}$.

This is the same as for ΔZ_2 .

30 The conclusion is that ΔZ_3 (the change of image focal distance) is $+.018 \text{ mm}$, the same as ΔZ_2 (the change of the physical distance between optics and media), so the head is "thermally compensated."

-21-

Figs. 20A and 20B show an integrated optics tracking sensor 75 attached to a magnetic read/write head 15.

A hole 74 in the magnetic head 15 allows light from the edge mounted laser 76 to be incident on the magnetic disk 10. The repeatable reflective light is incident upon the detector 77 in the integrated optics 75. Integrated optics 75 consists of optical elements and an optical path built up much as integrated circuits are, by lithographic means with parts of the optical path being essentially like optical fibers or waveguides built into the layers and patterns. Such a head has integrated HOE's, lasers, detectors and waveguides as described in: "FOCUSING GRATING COUPLER DESIGN METHOD USING HOLOGRAPHIC OPTICAL ELEMENTS", Patrick J. Cronkite and George N. Lawrence, Feb. 15, 1988, Vol. 27, No. 4; APPLIED OPTICS, PP. 679-683.

Magnetic head 15 has the usual magnetic pole piece 78 and groove 79. As explained more fully in the Losee, et al U.S. Patents 4,414,592 and 4,975,794, groove 79, flat area 80, and rounded area 81 provide good coupling of the head to a floppy disk. The oval outline of a very slight edge, which is very obtuse and between the flat and round zones, is denoted 82.

The materials of the substrates for the integrated optics 75 and the magnetic head 15 may be different, but the two are handled with very similar processing steps, being cut and polished to fine dimensional tolerances. The two devices can be made such that the focal distance of the optical part is precisely equal to the thickness of the magnetic head such that the two small "blocks" can be stacked with their edges referenced and cemented, and the optical spots come to be co-related in position precisely as they need to be relative to the magnetic head pole pieces.

While particular embodiments of the invention have been shown and described, various modifications are within

-22-

the true spirit and scope of the invention. The appended claims are, therefore, intended to cover all such modifications.

WHAT IS CLAIMED IS:

1. In a disk storage system for reading data from or writing data to a disk surface having a rotational axis and a plurality of data tracks about the rotational axis including:
 - means for rotating said disk surface about the rotational axis;
 - a head positioned adjacent to the disk surface for reading and/or writing data from said tracks;
 - means for positioning said head with respect to said disk surface; and
 - a servo system for controlling said means for positioning, said servo system being responsive to a servo error signal;
- the improvement comprising:
 - pre-recorded optical servo tracks for indicating the radial position of said head with respect to said disk;
 - means for producing an optical interference pattern having a fringe spacing related to the spacing of said servo tracks;
 - said interference pattern being incident upon said servo tracks; and
 - means for generating said servo error signal which is the convolution of said interference pattern and said servo tracks.
2. The system recited in claim 1 wherein said servo tracks are pre-recorded concentrically with said data tracks.
3. The system recited in claim 1 wherein said fringe spacing is equal to the pitch of said servo tracks.
4. The system recited in claim 1 wherein said interference pattern is reflected from said servo tracks, said system further comprising:

-24-

an optical detector, the reflected light being incident on said detector to produce said servo error signal.

5 5. The system recited in claim 1 further comprising:

 means for generating two optical interference patterns, one out of phase with the other.

 6. The system recited in claim 5 and a binary cell photodetector, said two optical interference patterns
10 being convolved with the servo tracks on said disk, one of the convolved optical patterns being incident on one of the binary cells of said photodetector to produce said servo error signal, the other of the convolved optical patterns being incident on the other of the binary cells to produce
15 a quadrature servo error signal.

 7. The system recited in claim 6 wherein said interference pattern is divided into two independent beams with a small angular difference therebetween to create two separate interference patterns at the focal plane.

20 8. The system recited in claim 7 wherein said angular difference is produced by:

 a wedge prism dividing the beam in a direction nearly orthogonal to that of the optical interference, the reflected image of said two interference patterns being
25 focused onto two cells of said detector resulting in said quadrature signal.

 9. The system recited in claim 7 wherein said angular difference is produced by:

 a holographic optical element dividing the beam
30 in a direction nearly orthogonal to that of the optical interference, the reflected image of said two interference

-25-

patterns being focused onto two cells of said detector resulting in said quadrature signal.

10. The system recited in claim 4 further comprising a collecting lens for focusing reflected light
5 on said detector.

11. The system recited in claim 1 wherein said means for producing an interference pattern includes a coherent light source.

12. The system recited in claim 11 further
10 comprising an aperture plate containing two slits producing two crossed beams of coherent light.

13. The system recited in claim 12 and an imaging lens, or HOE, wherein the spacing between said two slits and the imaging lens focal length or HOE length
15 determines the relative angle between said two beams, the spatial frequency of said interference pattern being determined by said relative angle.

14. The system recited in claim 13 wherein said slit spacing and the focal length of said imaging lens are
20 selected to produce a beam angle of approximately 2.2° at a wavelength of about 780 nm to achieve fringe spacing of approximately 20 μm .

15. The system recited in claim 1 wherein said means for producing an optical interference pattern is a
25 holographic optical element.

16. The system recited in claim 1 wherein said servo tracks are pre-recorded on said disk further comprising:

a fixed grating;

-26-

means for generating another optical interference pattern, said other optical interference pattern being incident upon said fixed grating; and

5 a multiple cell detector producing a signal responsive to light incident upon said servo tracks and another signal responsive to light incident upon said fixed grating.

17. The system recited in claim 15 further comprising:

10 means for generating two further optical interference patterns, each being out of phase with the first recited two interference patterns; and

a quadrant photodetector producing quadrature signals for each pair of interference patterns, said
15 signals being differenced to provide two quadrature signals without a dc component.

18. An optical tracking servo system for a disk storage system in which information is read from or written to a plurality of data tracks about the rotational axis of
20 the disk by a head comprising:

optical servo tracks pre-recorded in relation to said data tracks for indicating the radial position of said head with respect to said disk;

25 means for producing an optical interference pattern having a fringe spacing related to the spacing of said servo tracks, said interference pattern having a length which extends over several tracks;

means for imaging said interference pattern on said servo tracks; and

30 means for generating a servo error signal which is the convolution of said interference pattern and said servo tracks.

19. The system recited in claim 18 further comprising:

-27-

means for generating a second optical interference pattern, said second optical interference pattern being out of phase with the first recited optical interference pattern, both of said interference patterns
5 being imaged on said disk surface.

20. The system recited in claim 19 and a binary cell detector, said first and second optical interference patterns being convolved with the servo tracks on said disk, the convolved optical patterns being incident on the
10 binary cells of said photodetector to produce said servo error signal and a quadrature servo error signal.

21. The system recited in claim 18 further comprising:

means for dividing said interference pattern
15 into two independent beams with a small angular difference therebetween to create two separate interference patterns at the focal plane.

22. The system recited in claim 21 wherein said means for dividing said interference pattern comprises:
20 a wedge prism dividing the beam in a direction nearly orthogonal to that of the optical interference, the convolved image of said two interference patterns being focused onto two cells of said detector resulting in said servo error signal and a quadrature servo error signal.

25 23. The system recited in claim 18 wherein said means for producing an interference pattern includes a coherent light source and an aperture plate containing two slits producing two crossed beams of light.

30 24. The system recited in claim 23 and an imaging lens wherein the spacing between said two slits and the lens focal length determines the relative angle between

-28-

said two beams, the spatial frequency of said interference pattern being determined by said relative angle.

25. The system recited in claim 18 wherein said servo tracks are a grating which is fixed with respect to said head, said interference pattern being incident upon said grating; and

said means for generating a servo error signal including a detector for detecting light which is the convolution of said interference pattern and said grating.

26. The system recited in claim 25 wherein said grating has a flag area different from the remainder of said grating, said flag area marking a reference position of said head with respect to said disk; and

means responsive to the convolution of said interference pattern and said grating for indicating that said head is at said reference position.

27. The system recited in claim 26 further comprising:

a radial position counter for counting increments of radial movement of said head;

said counter being reset by said means for indicating that said head is at said reference position.

28. The system recited in claim 26 wherein said grating comprises successive light and dark bars.

29. The system recited in claim 28 wherein said flag area has at least one light bar and at least one dark bar having significantly wider width than the remainder of said bars.

30. The system recited in claim 28 wherein said flag area is a void of said successive light and dark bars.

-29-

31. The system recited in claim 30 wherein said void is narrower than the width of said interference pattern which is imaged on said grating.

32. The system recited in claim 25 further comprising:

means for generating a second optical interference pattern, said second optical interference pattern being out of phase with the first recited optical interference pattern, both of said interference patterns being imaged on said grating.

33. The system recited in claim 32 further comprising:

means for generating a third optical interference pattern imaged on said grating;
said grating having a flag area marking a reference position of said head with respect to said disk;
said flag area being in the path of said third optical interference pattern.

34. The system recited in claim 18 wherein said means for imaging said interference pattern includes a holographic optical element and a lens molded on a block of transparent plastic, said holographic optical element being formed on one flat surface of said block of transparent plastic and said lens being molded on the opposite surface to provide temperature compensation of the optical elements.

35. The system recited in claim 18 wherein said head is a magnetic head for reading magnetically recorded data in said data tracks, and wherein said means for generating a servo error signal comprises an optical head responsive to the convolution of said interference pattern and said servo tracks;



said magnetic head and said optical head being attached as a common structure.

-30-






36. The system recited in claim 35 wh r in said optical head includes integrated optical elements attached to said magnetic head.

37. The system recited in claim 36 wherein said
5 integrated optics includes a laser diode source of light, holographic optical elements for producing said optical interference pattern, and a photodetector for generating said servo error signal.

1/14





**FIG. 2**

2/14



3/4

FIG. 5



4/14




FIG. 9




FIG. 8A




FIG. 9A




FIG. 8




FIG. 12




FIG. 12A

5/14




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B

6/14




FIG. 13




FIG. 14

7/14




FIG. 15A




FIG. 15B

8/14




FIG. 16

9/14




FIG. 17A




FIG. 17B

10/14




FIG. 18

11/14




FIG. 18A




FIG. 18B




FIG. 18C

12/14




FIG. 19A




FIG. 19B

13/14




FIG. 20B




FIG. 20A




FIG. 20C




FIG. 21

INTERNATIONAL SEARCH REPORT

International Application No. **PCT/US91/04255**

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) * According to International Patent Classification (IPC) or to both National Classification and IPC IPC(5): G11B 7/00 U.S. CL.: 369/44.26											
II. FIELDS SEARCHED <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Minimum Documentation Searched ⁷</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 25%; border-bottom: 1px solid black;">Classification System</th> <th style="border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="vertical-align: top; padding: 5px;">U.S.</td> <td style="padding: 5px;"> 369/100, 103, 109, 13, 44.26; 250/201.5 350/3.7; 356/358 </td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸</div>			Classification System	Classification Symbols	U.S.	369/100, 103, 109, 13, 44.26; 250/201.5 350/3.7; 356/358					
Classification System	Classification Symbols										
U.S.	369/100, 103, 109, 13, 44.26; 250/201.5 350/3.7; 356/358										
III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%; padding: 5px;">Category ⁹</th> <th style="width: 60%; padding: 5px;">Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²</th> <th style="width: 30%; padding: 5px;">Relevant to Claim No. ¹³</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">Y</td> <td style="padding: 5px;">US, A, 4,525,826 (NAKAMURA) 25 June 1985, See Figure 2 and column 2.</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-37</td> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">Y</td> <td style="padding: 5px;">US, A, 4,253,723 (KOJIMA) 03 March 1981, See Figure 6A and 14. Also, see column 6.</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-37</td> </tr> </tbody> </table>			Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	Y	US, A, 4,525,826 (NAKAMURA) 25 June 1985, See Figure 2 and column 2.	1-37	Y	US, A, 4,253,723 (KOJIMA) 03 March 1981, See Figure 6A and 14. Also, see column 6.	1-37
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³									
Y	US, A, 4,525,826 (NAKAMURA) 25 June 1985, See Figure 2 and column 2.	1-37									
Y	US, A, 4,253,723 (KOJIMA) 03 March 1981, See Figure 6A and 14. Also, see column 6.	1-37									
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>¹⁰ Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>											
IV. CERTIFICATION <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top; padding: 5px;"> Date of the Actual Completion of the International Search <div style="text-align: center; font-weight: bold;">22 JULY 1991</div> </td> <td style="width: 50%; vertical-align: top; padding: 5px;"> Date of Mailing of this International Search Report <div style="text-align: center; font-weight: bold; font-size: 1.2em;">01 OCT 1991</div> </td> </tr> <tr> <td style="vertical-align: top; padding: 5px;"> International Searching Authority <div style="text-align: center; font-weight: bold;">ISA/US</div> </td> <td style="vertical-align: top; padding: 5px;"> Signature of Authorized Officer: <i>Nabil Hindi</i> <div style="text-align: center; font-weight: bold;">NABIL HINDI INVENTOR: NGUYEN HO INTERNATIONAL DIVISION</div> </td> </tr> </table>			Date of the Actual Completion of the International Search <div style="text-align: center; font-weight: bold;">22 JULY 1991</div>	Date of Mailing of this International Search Report <div style="text-align: center; font-weight: bold; font-size: 1.2em;">01 OCT 1991</div>	International Searching Authority <div style="text-align: center; font-weight: bold;">ISA/US</div>	Signature of Authorized Officer: <i>Nabil Hindi</i> <div style="text-align: center; font-weight: bold;">NABIL HINDI INVENTOR: NGUYEN HO INTERNATIONAL DIVISION</div>					
Date of the Actual Completion of the International Search <div style="text-align: center; font-weight: bold;">22 JULY 1991</div>	Date of Mailing of this International Search Report <div style="text-align: center; font-weight: bold; font-size: 1.2em;">01 OCT 1991</div>										
International Searching Authority <div style="text-align: center; font-weight: bold;">ISA/US</div>	Signature of Authorized Officer: <i>Nabil Hindi</i> <div style="text-align: center; font-weight: bold;">NABIL HINDI INVENTOR: NGUYEN HO INTERNATIONAL DIVISION</div>										